

Specifications for EZ Slitters

	Models 270/272	Models 280/282
Setup:	Average 5 Seconds	Average 5 Seconds (additional if scoring, add 15 seconds)
Slitting Speed:	Variable, 0 to 80 in/s	Variable, 0 to 80 in/s
Material:	Slit corrugated Boxboard up to Triplewall 1200 lb. test	Slit corrugated material thru Triplewall 1200 lb. test Score boxboard, thru 600 lb. Doublewall
Slit up to:	Model 270: 38"/965mm from any edge Model 272: 50"/1270mm from any edge	Model 280: 38"/965mm from any edge Model 282: 50"/1270mm from any edge
Slit Depth:	Model 270: From 1/4" / 6mm to 38"/965mm Model 272: From 1/4" / 6mm to 50"/1270mm	Model 280: From 1/4" / 6mm to 38"/965mm Model 282: From 1/4" / 6mm to 50"/1270mm
Scoring:	Up to 4 scores, while slitting	Up to 4 scores, while slitting 4 scoring heads standard with slitter; additional scoring heads optional. Minimum distance between scores: 3" / 76mm
Footprint:	11'3.3m Wide 5'1.5m Deep 4'1.22m High	Model 280: 11'3.3m Wide, Model 282: 12'3.6m Wide 5'1.5m Deep 4'1.22m High
Weight, Net:	Model 270: 800 lb/365 kg Model 272: 900 lb/410 kg	Model 280: 900 lb/410 kg Model 272: 1000 lb/455 kg
Weight, Shipping:	Model 270: 1000 lb/455 kg Model 272: 1100 lb/500 kg	Model 280: 1100 lb/500 kg Model 282: 1200 lb/545 kg
Electrical:	4a @ 100-120 VAC or 2a @ 200-240 VAC, 50/60Hz, 1 ph	4a @ 100-120 VAC or 2a @ 200-240 VAC, 50/60Hz, 1 ph
Warranty:	One year on all parts.	One year on all parts.